

HD100

New Product!



High Current Discrete Output Stereo Power Amplifier

100 Watts RMS @ 8 ohms
 150 Watts RMS @ 4 ohms
 300 Watts RMS @ 8 ohms Bridged

The Power to Drive Multi-Room Systems and is the perfect companion to any autoformer protected multi-room system. The HD100 delivers superior transient response, particularly bass transients when connected to multi-room impedance matching systems. Its extraordinary sweet and musical soundstage has found acceptance in the most demanding applications.

Fast and Effective Level Calibration with clipping indicators and detented level controls, combining to enable you to preset safe non-clipping levels with the perfect left right balance based on the installed preamp's highest volume setting. The result: your installations become bulletproof with no possibility of teenager abuse and service calls.

Professional Installation with sleek brushed black aluminum chassis, rack mount and detented level controls enable you to attractively flush mount or place on shelves. Equipped with balanced and unbalanced inputs via 1/4" phone and XLR connectors. For residential applications, the HD100 ships with a six foot RCA to Phone Audio Umbilical cable. Speaker wire connects to either gold binding posts or reliable Neutrik connectors for easy and quick connections.

Fanless Cooling with the unique chassis design to force a convection flow of cooling air over the heat sinks. As a result no fan is necessary with the HD100.

Dimensions: 17.25"W x 3.25"H x 8.25"D
 Weight: 25 lbs.

HD100	High current power amplifier
-------	------------------------------

AMP10

Mini Stereo
 Power Amplifier



10 Watts RMS @ 8 ohms
 14 Watts RMS @ 4 ohms

Achieves Real World 95 dB Plus Levels with most in-wall and in-ceiling speakers. Showing sensitivity in the 85 to 90 dB range, the AMP10 will conservatively drive speakers far louder than most applications demand. The secret behind the AMP10's performance is its high current output stage and sophisticated circuit design.

Installation Flexibility with low-voltage power supply designed to make installation of the AMP10 easy in hard to reach places. Now, you can place real-world power in distant locations; near TV sets, local CD players and other line level sources. Adjustable front gain control enables installers to compensate for low level sources.

Inexpensive Multi-Sourcing Via AB Switches. Typically, customers are attracted to the idea of local TVs and CD players switched through local speakers. However, the high cost of most power amplifiers makes the idea less attractive to many. Now with the introduction of the AMP10, anyone can afford multi-source systems.

Professional Protection Circuitry guaranteed for a lifetime, and we know it will do it. Every contingency from accidental dead shorts to thermal overload is covered. The AMP10 is forgiving to abusive clients, shutting itself off when too hot, but resetting automatically when internal temperatures return to normal. No hard resets necessary.

Dimensions: 8"W x 2.5"H x 5"D
 Weight: 8 lbs.

Includes Power Supply

AMP10	Mini stereo power amplifier
-------	-----------------------------

LITTLE AMP

Stereo Headphone Power Amplifier

LittleAmp enables headphones to be driven from any source directly. Feeding low level outputs from any line level source through the LittleAmp's 10dB of gain, providing comfortable listening levels from any stereo headphone. Order the LittleAmp-2 and get an additional RCA output. Can also be used as a line level distribution amp.

1/3 Watt Power
 RCA or Headphone Output
 Board or Chassis Versions
 1" x 2"(board) 6"W x 2.75"H x 5"D(chassis)

Please specify RCA or 1/8" outputs when ordering

LITTLE AMP-B	Circuit Board with Pigtails (requires 12v power supply)
LITTLE AMP-C	Chassis with Volume Control
LITTLE AMP-2	Chassis with Volume Control and 2 RCA Outputs

